Renown Baseboard Stripper (REN05022-AM / 880279)

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Renown Baseboard Stripper (REN05022-AM / 880279)

Product Number: A00806

Product Use: Wax Stripper.

Manufacturer/Supplier: Interline Brands

701 San Marco Blvd. Jacksonville. FL 32207

Phone Number: 1-866-412-6726

D.O.T. Emergency Phone: Chemtrec 1-800-424-9300

Date of Preparation: November 15, 2012 **Revision #:** 2.0

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER

CORROSIVE MATERIAL - MAY CAUSE BURNS. MAY CAUSE RESPIRATORY SENSITIZATION. MAY CAUSE SKIN SENSITIZATION. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED. HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: Irritating to eyes. May cause burns.

Skin: Irritating to skin. May cause burns. May cause sensitization by skin contact.

Ingestion: Not a normal route of exposure. May cause burns. Harmful: may cause lung

damage if swallowed.

Inhalation: May cause respiratory tract irritation. May cause respiratory sensitization.

May cause asphyxiation. This product may be aspirated into the lungs and

HMIS: See Section 15

cause chemical pneumonitis.

Chronic Effects: May cause sensitization by inhalation and skin contact.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Vapours may cause drowsiness and dizziness.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Renown Baseboard Stripper (REN05022-AM / 880279)

Section 3:	COMPOSITION	ON / INFORM	ATION ON	INGREDIENTS
Je ction J.	COMI COLL			INCINEDIENTO

Ingredient	CAS#	Wt. %
Isopropanol	67-63-0	5 - 10
Isobutane	75-28-5	5 - 10
Monoethanolamine	141-43-5	3 - 7
Ethylene glycol monobutyl ether	111-76-2	1 - 5
Ethanol	64-17-5	1 - 5
Propane	74-98-6	0.5 - 1.5

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove

contaminated clothing and shoes. Wash clothing before reuse. Call a physician

if irritation develops and persists.

Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon, oxides of nitrogen.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Containers may explode when heated. Keep upwind of fire. Wear

full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

Environmental Precautions: Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Renown Baseboard Stripper (REN05022-AM / 880279)

Methods for Clean-Up: Scoop up material and place in a disposal container. Provide ventilation.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Launder contaminated clothing before reuse. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container in a well-ventilated place. Do not store at temperatures above 49 ℃ / 120 F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

	Exposure	Exposure Limits		
Ingredient	OSHA-PEL	ACGIH-TLV		
Isopropanol	400 ppm	200 ppm		
Isobutane	Not available.	1000 ppm		
Monoethanolamine	3 ppm	3 ppm		
Ethylene glycol monobutyl ether	50 ppm	20 ppm		
Ethanol	1000 ppm	1000 ppm		
Propane	1000 ppm	1000 ppm		

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment: HMIS: See Section 15

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and

safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear. Color: Colorless. Odor: Solvent.

Odor Threshold: Not available.

Physical State: Gas/Pressurized Liquid.

:Ha 12

Not available. **Viscosity: Freezing Point:** Not available. Not available. **Boiling Point:**

Renown Baseboard Stripper (REN05022-AM / 880279)

Flash Point:

Evaporation Rate:

< 1 (Water = 1)

Lower Flammability Limit:

Not available.

Vapor Pressure:

Not available.

Not available.

Not available.

Not available.

Specific Gravity: 0.984 (Liquid concentrate)

Solubility in Water: Complete.

Coefficient of Water/Oil Distribution: Not available.

Auto-ignition Temperature: Not available.

Percent Volatile, wt. %: Not available.

VOC content, wt. %: 31.7% (US federal/CARB/OTC/LADCO)

VOC content, g/L: Not available.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials. **Incompatible Materials:** Acids. Alkali metals. Copper.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon, oxides of pitrogen

oxides of nitrogen.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD ₅₀ (oral)	LC ₅₀
Isopropanol	4396 mg/kg, rat	72.6 mg/L 4hr, rat
Isobutane	Not available.	658 mg/L 4hr, rat
Monoethanolamine	1720 mg/kg, rat	Not available.
		450 ppm 4hr, rat;
Ethylene glycol monobutyl ether	470 mg/kg, rat	2.21 mg/L 4hr, rat
Ethanol	7060 mg/kg, rat	124.7 mg/L 4hr, rat
Propane	Not available.	658 mg/L 4hr, rat

Eye: Irritating to eyes. May cause burns. Symptoms may include discomfort or pain, excess

blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: Irritating to skin. May cause burns. May cause sensitization by skin contact.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Ingestion: Not a normal route of exposure. May cause burns. Harmful: may cause lung

damage if swallowed.

Inhalation: May cause respiratory tract irritation. May cause respiratory sensitization. May

4/7

cause asphyxiation. This product may be aspirated into the lungs and cause

chemical pneumonitis. Vapours may cause drowsiness and dizziness.

Renown Baseboard Stripper (REN05022-AM / 880279)

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by OSHA criteria. **Carcinogenicity:** Hazardous by OSHA criteria.

Ingredient Chemical Listed as Carcinogen or Potential Carcinogen *

IsopropanolG-A4, I-3IsobutaneNot listed.MonoethanolamineNot listed.Ethylene glycol monobutyl etherG-A3, I-3

Ethanol G-A3, I-1 (in alcoholic beverages), O

Propane Not listed.

Mutagenicity: Hazardous by OSHA criteria.

Reproductive Effects: Not hazardous by OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by OSHA criteria.

Embryotoxicity: Not hazardous by OSHA criteria.

Respiratory Sensitization: Hazardous by OSHA criteria.

Skin Sensitization: Hazardous by OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D, Limited Quantity

Section 15: REGULATORY INFORMATION

Federal Regulations

US: MSDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200).

^{*} See Section 15 for more information.

Renown Baseboard Stripper (REN05022-AM / 880279)

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Isopropanol	Not listed.	Not listed.	Not listed.	Yes.
Isobutane	Not listed.	Not listed.	Not listed.	Not listed.
Monoethanolamine	Not listed.	Not listed.	Not listed.	Not listed.
Ethylene glycol monobutyl ether	Not listed.	Not listed.	Not listed.	Yes.
Ethanol	Not listed.	Not listed.	Not listed.	Not listed.
Propane	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	USA
	TSCA
Isopropanol	Yes.
Isobutane	Yes.
Monoethanolamine	Yes.
Ethylene glycol monobutyl ether	Yes.
Ethanol	Yes.
Propane	Yes.

HMIS - Hazardous Materials Identification System

Health - 2* Flammability - 1 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 2 Fire - 1 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

6 / 7 November 15, 2012

Renown Baseboard Stripper (REN05022-AM / 880279)

Section 16: OTHER INFORMATION

Disclaimer:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Prepared for: Interline Brands

Phone: 1-866-412-6726