

Material Safety Data Sheet

Perma Patch

1. PRODUCT MANUFACTURER / MSDS PREPARATION INFORMATION

Product Manufacturer/ McAsphalt Industries Ltd. **Supplier:** 8800 Sheppard Ave. East

Scarborough, Ontario

M1B 5R4

(416) 281-8181 MSDS Prepared By: Engineering and Risk Management

Product: Perma-Patch

Product Use: Asphalt, Cold Mix For Pot Hole Repair

Revision Date: February 3, 2010 **Supercedes:** December 15, 2008

EMERGENCY NUMBER: CANUTEC - (613) 996-6666

WHMIS: B3 Combustible Liquid, D2B Other Toxic Effects (untested)

Workplace Label: Health-2 Fire-2 Reactivity - 0

Transport: Elevated Temperature Liquid, Flammable, NOS, Class 3, UN3256, PGIII

2. INGREDIENTS / COMPOSITION

COMPONENT(S)	CAS#	% (w/w)	LD_{50}	LC_{50}	PIN
Fuel Oil	68476-30-2	10-30	N/A	N/A	UN1202
Asphalt	8052-42-4	50-80	N/A	N/A	N/A
Asphalt Additive	Proprietary	1-5	N/A	N/A	N/Av

3. PHYSICAL DATA

Physical State:LiquidAppearance: BlackSpecific Gravity:0.94-1.0@ 15°COdour: Tar, fuelFreezing Point:N/AOdour Threshold: N/ABoiling Point:>160°CSolubility: Not water solubleVapour Pressure:N/AEvaporation Rate: N/A

Vapour Density: 3-4 (air=1) **pH:** N/A

4. FIRE & EXPLOSION HAZARD

Flash Point & Method: >80°C (COC) Flammability Limits: 0.7-6.5% (Estimate)

Auto-Ignition Temperature: N/A

Fire Fighting Media: CO₂, Dry Chemical, Water spray with caution

Explosion/Flammability: Eliminate sources of ignition, (ie flames/sparks) may be sensitive to static

discharge.

Hazardous Combustion Products: CO, NO_x, SO_x, sulfur products

THIS PRODUCT IS COMBUSTIBLE!! USE CAUTION WHEN HANDLING ANY CONTAINERS(INCLUDING EMPTY) THEY MAY CONTAIN EXPLOSIVE AIR/FUEL MIXTURES.

Perma Patch Page 1 of 2

5. REACTIVITY DATA

Stability: Stable

Incompatible Materials: Water, Strong Oxidizers

Conditions of Reactivity: N/A

Hazardous Decomposition Products: CO, SO_x, NO_x, other Sulfur compounds

Synergistic Products: None

6. HEALTH HAZARD INFORMATION

Skin: can cause skin irritation, dermatitis. Skin defatting with chronic exposure

Eyes: yes – irritation, can cause conjunctivitis

Inhalation: yes, irritation of nose, respiratory tract, nausea, headaches

Exposure Limits: 5mg/M³ Asphalt fumes (Ontario) check local regulations

100 PPM for Fuel oil

Use extra caution in confined spaces, ensure adequate ventilation to limits vapour exposure

Ingestion: yes, - (ingestion unlikely) do not induce vomiting. **No known carcinogenic, teratogenic or reproductive effects.**

May contain traces of benzene, a known carcinogen.

7. PREVENTATIVE MEASURES

Personal Protective Equipment: Rubber gloves, goggles, face shield, respirator with organic vapour cartridge **Handling/Shipping/Storage: Do not cut or weld on or near empty/full containers!**

Flammable/explosive vapours may be present in all containers including empty containers.

Do not store near flames or heat. Ground containers when transferring.

Ventilation: Ensure adequate ventilation, to limit exposure & remove flammable vapours

Disposal: See appropriate federal, provincial, municipal regulations

LEAKS AND SPILLS: Contain with earth or sand, allow to cool and harden. Eliminate sources of ignition.

Notify authorities when in water, or large spills.

8. FIRST AID

SKIN: Wash with soap and water, if irritation persists, seek medical aid

EYES: Gently flush with lots of water. Seek Medical Help. **INHALATION:** Remove victim to fresh air. Seek Medical Help. **INGESTION:** Give lots of water to drink. Seek Medical Help.

9. NOTE

The information contained herein relates only to this product or material and may not be valid when used in combination with any other product or material or in any process. If the process is not to be used under conditions, which are normal or reasonably foreseeable, this information cannot be relied upon as complete or applicable. The information contained herein is based upon the information available at the indicated date of preparation, the above supplier assumes no liability whatsoever for the accuracy or completeness of the information.

Perma Patch Page 2 of 2