SAFETY DATA SHEET

	- PRODUCT AND COMPANY	IDENTIFICATION
25790, 25793 CHEMICAL FAMILY Organic	25300, 25431, 25551,	HMIS CODES Health 1 Flammability 2 Reactivity 0 PPI B 25552, 25631, 25633, 25780,
USE Pipe Thread Sealant MANUFACTURER'S NAME The RectorSeal Corpo 2601 Spenwick Drive Houston, Texas 7705		EMERGENCY TELEPHONE NO. Chemtrec 24 Hours (800)424-9300 USA (703)527-3887 International
DATE OF VALIDATION January 23, 2015 DATE OF PREPARATION January 9, 2013		TECHNICAL SERVICE TELEPHONE NO. (800)231-3345 or (713)263-8001
Section 2 HAZARDS IDENTIFICATION		
EMERGENCY OVERVIEW OSHA Hazards Combustable TARGET ORGANS Not Classified GHS CLASSIFICATION PHYSICAL HAZARDS Combustable liquid (Cat HEALTH HAZARDS Acute Toxicity: Oral: Not Classified Dermal: Not Classified Inhalation: Not Classified Inhalation: Not Classified Skin Corrosion/Irritati Serious Eye Damage/Eye Skin Sensitization: No Respiratory Sensitizati Germ Cell Mutagenicity: Carcinogenicity: See Se Reproductive Toxicology Target Organ Systemic T Aspiration Toxicity: No	fied on: Not Classified Irritation: Not Class t Classified on: Not Classified Not Classified ction 11 : Not Classified oxicity - Single Expo oxicity - Repeated Ex	sure: Not Classified
Precautionary Statement P102 - Keep out of reac	ritant f swallowed. n contact with skin. respiratory irritati s h of children.	statements on, and drowsiness or dizziness. s/hot surfaces No smoking

SDS 0011

http://www.rectorseal.com/web-media/RectorSeal-No-5.html[6/12/2016 4:23:23 PM]

P240 - Ground/Bond container and receiving equipment P261 - Avoid breathing dust/fume/gas/mist/vapors/sprav P262 - Do not get in eyes, on skin, or on clothing. P264 - Wash hands thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362 - Take off contaminated clothing and wash before reuse. EUH066 - Repeated exposure may cause skin dryness or cracking Precautionary Statements - EU No. 1272/2008 -SUMMARY OF ACUTE HAZARDS Irritation to eves, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration. ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS INHALATION Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness. EYE CONTACT Watering, blurred vision, inflammation and irritation which can result in corneal injury. SKIN CONTACT Irritation, dermatitis. INGESTION Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion. SUMMARY OF CHRONIC HAZARDS Skin irritation and dermatitis. Possible liver and kidney damage. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures. Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS \_\_\_\_\_ INGREDIENT: Diacetone Alcohol PERCENTAGE BY WEIGHT: 20-30 CAS NUMBER: 123-42-2 EC# : 204-626-7 \_\_\_\_\_ Section 4 -- FIRST AID MEASURES \_\_\_\_\_ If INHALED: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential. Wash with soap and water. If irritation occurs, seek If on SKIN: medical attention. If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention. If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. Section 5 -- FIRE FIGHTING MEASURES \_\_\_\_\_ EXTINGUSING MEDIA Foam, dry chemical, carbon dioxide or water fog. SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10). UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point.

Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers. \_\_\_\_\_ Section 6 -- ACCIDENTAL RELEASE MEASURES \_\_\_\_\_ STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup. Section 7 -- HANDLING AND STORAGE \_\_\_\_\_ PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames. OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN. \_\_\_\_\_ Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION \_\_\_\_\_ INGREDIENT UNITS Diacetone Alcohol ACGIH TLV 50 ppm OSHA PEL 50 ppm RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators. VENTILATION - LOCAL EXHAUST: Acceptable SPECIAL: Explosion-proof equipment. MECHANICAL (GENERAL): Preferable OTHER: N/A PROTECTIVE GLOVES: Wear rubber gloves. EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent) OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended. WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse. Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES \_\_\_\_\_ 

 BOILING POINT:
 322 F (161 C) @ 760mm Hg

 SPECIFIC GRAVITY (H20 = 1):
 1.38

 VAPOR PRESSURE (mm Hg):
 0.3 @ 68 F (20 C)

MELTING POINT: N/A VAPOR DENSITY (AIR = 1): 1.1 EVAPORATION RATE (ETHYL ACETATE = 1): 0.14 AFPLAKANCE/ODOR: Yellow Paste/Mild Odor SOLUBILITY IN WATER: 22% VOLATILE ORGANIC COMPOUNDS(VOC)Content (Theoretical Percentage By Weight):23% or (317 g/L)Flash POINT150 F (65 C) SETA CCLOWER EXPLOSION LIMITN/DUPPER EXPLOSION LIMITN/D Section 10 -- STABILITY AND REACTIVITY \_\_\_\_\_ STABILITY: Stable CONDITIONS TO AVOID: Heat, sparks, open flames, and strong oxidizing.

Temperatures above 500 F (260 C). INCOMPATIBILITY (MATERIALS TO AVOID): Gaseous oxygen, strong oxidizing materials, molten alkali metals. HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2 and fragmented hydrocarbons. HAZARDOUS POLYMERIZATION: Will not occur. \_\_\_\_\_ Section 11 -- TOXICOLOGY INFORMATION \_\_\_\_\_ CHRONIC HEALTH HAZARDS No ingredients in this product is an IARC, NTP or OSHA Lister carcinogen. TOXICOLOGY DATA Ingredient Name \_\_\_\_\_ Diacetone Alcohol Oral-Rat LD50:4000 mg/kg Inhalation-Human TCLo: 100 ppm \_\_\_\_\_ Section 12 -- Ecological Information \_\_\_\_\_ ECOLOGICAL DATA Ingredient Name -Diacetone Alcohol Food Chain Concentration Potential N/A WATERFOWL TOXICITY N/A N/A BOD AOUATIC TOXICITY N/A Section 13 -- DISPOSAL CONSIDERATIONS Waste Classification: Non-regulated solid waste Disposal Method: Approved landfill Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution. Section 14 -- TRANSPORTATION INFORMATION \_\_\_\_\_ DOT: Non-Regulated OCEAN (IMDG): Non-Regulated AIR (IATA): Non-Regulated WHMIS (CANADA): Non-Regulated \_\_\_\_\_ Section 15 -- REGULATORY INFORMATION \_\_\_\_\_ REGULATORY DATA Ingredient Name \_\_\_\_\_ Diacetone Alcohol SARA 313 N/A TSCA Inventory Yes CERCLA RQ N/A RCRA Code N/A \_\_\_\_\_ Section 16 -- OTHER INFORMATION \_\_\_\_\_ This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001