

SAFETY DATA SHEET

Revision Date 21-Apr-2016 Version 2

1. IDENTIFICATION

Product identifier

Product Name 26MA POWERBEAD HIGH TEMP RED RTV SILICONE 7.25 OZ AE

Other means of identification

Product Code 81915 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address <u>Distributor</u>

ITW Permatex Canada
6875 Parkland Blvd. 35 Brownridge Road, Unit 1
Solon, OH 44139 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Gases under pressure Compressed gas

Label elements

Emergency Overview

Warning

Contains gas under pressure; may explode if heated



Appearance Red Physical state Paste Odor Acetic acid

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity 12.3 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), HYDROTREATED	64742-46-7	3 - 7	*
MIDDLE			
NITROGEN	7727-37-9	1 - 5	*
ACETIC ACID	64-19-7	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aiderUse personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and skin. Contents under pressure. Do not puncture or incinerate

cans.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Flood with water to complete polymerization and scrape off

floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if

walked on.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wash thoroughly after handling. Do not puncture or incinerate cans.

Contents under pressure.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Store in a well-ventilated place. Protect from moisture.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

81915 - 26MA POWERBEAD HIGH TEMP RED RTV SILICONE 7.25 OZ AE

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETIC ACID	STEL: 15 ppm	TWA: 10 ppm	IDLH: 50 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m ³	TWA: 10 ppm
		(vacated) TWA: 10 ppm	TWA: 25 mg/m ³
		(vacated) TWA: 25 mg/m ³	STEL: 15 ppm
			STEL: 37 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Paste
Appearance Red
Odor Acetic acid

Odor threshold No information available

Property Values Remarks • Method

pH No information available

Melting point / freezing point No information available

Boiling point / boiling range Not Applicable Polymerization

Flash point > 93 °C / > 200 °F Evaporation rate No information available

Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit:

Lower flammability limit:

No information available

No information available

Vapor pressure <5 mm Hg

Vapor density >1 Air = 1 Relative density 1.05

Water solubilityNot applicablePolymerizationSolubility in other solventsNo information available

Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
Dynamic viscosity
Explosive properties
No information available

81915 - 26MA POWERBEAD HIGH TEMP RED RTV SILICONE 7.25 OZ AE

Other Information

Softening pointNo information availableMolecular weightNo information available

VOC Content (%) 3.0%

DensityNo information availableBulk densityNo information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides
Nitrogen oxides (NOx)
Acetic acid
Oxides of sulfur
Formaldehyde

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	= 7400 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	= 4.6 mg/L (Rat)4 h
ACETIC ACID 64-19-7	= 3310 mg/kg (Rat)	= 1060 mg/kg (Rabbit)	= 11.4 mg/L (Rat)4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

81915 - 26MA POWERBEAD HIGH TEMP RED RTV SILICONE 7.25 OZ AE

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Eyes, Respiratory system, Skin, Teeth.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 17289 mg/kg
ATEmix (dermal) 6094 mg/kg
ATEmix (inhalation-dust/mist) 4.8 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

82.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
DISTILLATES (PETROLEUM),	=	35: 96 h Pimephales promelas mg/L	-
HYDROTREATED MIDDLE		LC50 flow-through 10000: 96 h	
64742-46-7		Pimephales promelas mg/L LC50	
		static	
ACETIC ACID	-	79: 96 h Pimephales promelas mg/L	65: 48 h Daphnia magna mg/L
64-19-7		LC50 static 75: 96 h Lepomis	EC50 Static 47: 24 h Daphnia
		macrochirus mg/L LC50 static	magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
ACETIC ACID	-0.31
64-19-7	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETIC ACID	Toxic
64-19-7	Corrosive
	Ignitable

14. TRANSPORT INFORMATION

81915 - 26MA POWERBEAD HIGH TEMP RED RTV SILICONE 7.25 OZ AE

DOT

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.2 Emergency Response Guide 126

Number

IATA

UN/ID no ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

IMDG

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.2 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

Complies **TSCA** DSL/NDSL Complies Not Listed. **EINECS/ELINCS ENCS** Not Listed. Complies **IECSC** Complies **KECL PICCS** Complies **AICS** Complies

<u>Legend:</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardNoFire hazardNoSudden release of pressure hazardNoReactive HazardNo

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ACETIC ACID	5000 lb	-	-	X

64-19-7		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETIC ACID	5000 lb	=	RQ 5000 lb final RQ
64-19-7			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
TITANIUM DIOXIDE - 13463-67-7	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
AMORPHOUS SILICA	X	X	X
7631-86-9			
NITROGEN	X	X	X
7727-37-9			
IRON OXIDE	X	X	X
1309-37-1			
TITANIUM DIOXIDE	X	X	X
13463-67-7			
ACETIC ACID	X	X	X
64-19-7			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 1 Instability 0

HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 21-Apr-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet