SAFETY DATA SHEET

Issuing Date No data available **Revision Date** 14-Jan-2014 **Revision Number** 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier 207,208,210

Product Name **Oil Base DRYLOK Masonry Waterproofer**

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Waterproofing Sealers, Concrete/Masonry

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address
United Gilsonite Laboratories
1396 Jefferson Ave.
Dunmore
PA
18509
US
Phone:570-344-1202
Fax:570-969-7634
Email:rbarako@ugl.com
Contact Phone:570-344-1202

Emergency telephone number (800) 424-9300 Chemtrec

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements

Emergency Overview

Signal word **Warning**

Hazard Statements
Harmful if swallowed
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
May cause respiratory irritation. May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Flammable liquid and vapor

Appearance White **Physical State** Liquid **Odor** Aromatic

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)

Skin
If skin irritation or rash occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Inhalation
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Ingestion
Rinse mouth
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity
42% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals
Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade Secret
Portland cement	65997-15-1	10 - 30	*
Quartz	14808-60-7	10 - 30	*
Stoddard solvent	8052-41-3	10 - 30	*
Styrene acrylate copolymer	25085-34-1	5 - 10	*
Limestone	1317-65-3	5 - 10	*
Petroleum naphtha, light aromatic	64742-95-6	1 - 5	*
Mica	12001-26-2	1 - 5	*
1,2,4 Trimethylbenzene	95-63-6	1 - 5	*
Titanium dioxide	13463-67-7	1 - 5	*
Perlite	93763-70-3	1 - 5	*
1,3,5-Trimethylbenzene	108-67-8	1 - 5	*
Xylene, mixed isomers	1330-20-7	0.1 - 1	*
Cumene	98-82-8	0.1 - 1	*

* The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes. Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. If symptoms persist, call a physician.

Skin Contact May cause an allergic skin reaction. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately. Rinse mouth.

Protection of First-aiders Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation. Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. May cause sensitization of susceptible persons. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Dry chemical, CO2, water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable Extinguishing Media
CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical
Some may be transported hot.

Uniform Fire Code Combustible Liquid: II
Sensitizer: Liquid
Highly Toxic: Liquid

Hazardous Combustion Products
Carbon oxides.

Explosion Data
Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters
Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for Cleaning Up Dike far ahead of liquid spill for later disposal. Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Wear personal protective equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from moisture. Store away from other materials. Keep away from heat and sources of ignition. Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Portland cement 65997-15-1	TWA: 1 mg/m^3 particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m^3 total dust TWA: 5 mg/m^3 respirable fraction (vacated) TWA: 10 mg/m^3 total dust (vacated) TWA: 5 mg/m^3 respirable fraction TWA: 50 mppcf <1% Crystalline silica	IDLH: 5000 mg/m^3 TWA: 10 mg/m^3 total dust TWA: 5 mg/m^3 respirable dust
Quartz 14808-60-7	TWA: 0.025 mg/m^3 respirable fraction	TWA: 0.1 mg/m^3 (vacated)	IDLH: 50 mg/m^3 respirable dust TWA: 0.05 mg/m^3 respirable dust
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m^3 (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m^3	IDLH: 20000 mg/m^3 Ceiling: 1800 mg/m^3 15 min TWA: 350 mg/m^3
Limestone 1317-65-3	-	TWA: 15 mg/m^3 TWA: 5 mg/m^3 (vacated) TWA: 15 mg/m^3 (vacated) TWA: 5 mg/m^3	TWA: 5 mg/m^3 respirable dust TWA: 10 mg/m^3 total dust
Mica 12001-26-2	TWA: 3 mg/m^3	TWA: 20 mppcf (<1% crystalline silica) 3 mg/m^3 (vacated)	IDLH: 1500 mg/m^3 containing <1% quartz TWA: 3 mg/m^3 respirable dust
1,2,4 Trimethylbenzene 95-63-6	-	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m^3	TWA: 25 ppm TWA: 125 mg/m^3
Titanium dioxide 13463-67-7	TWA: 10 mg/m^3	TWA: 15 mg/m^3 total dust (vacated) TWA: 10 mg/m^3 total dust	IDLH: 5000 mg/m^3
Perlite 93763-70-3	-	(vacated) TWA: 15 mg/m^3 total dust (vacated) TWA: 5 mg/m^3 respirable fraction	TWA: 10 mg/m^3 total dust TWA: 5 mg/m^3 respirable dust
1,3,5-Trimethylbenzene 108-67-8	-	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m^3	TWA: 25 ppm TWA: 125 mg/m^3
Xylene, mixed isomers 1330-20-7	STEL: 150 ppm TWA: 100 ppm	-	
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m^3 (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m^3 (vacated) S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m^3

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering Measures
Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection None required for consumer use. If splashes are likely to occur:. Tight sealing safety goggles.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid		
Appearance	White	**Odor**	Aromatic
Color	No information available	**Odor Threshold**	No information available

Property	**Values**	**Remarks/ Method**
pH	UNKNOWN	None known
Melting/freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	40 C / 104 F	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Insoluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive Properties	No data available	
Oxidizing Properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability
Stable under recommended storage conditions.

Possibility of Hazardous Reactions
None under normal processing.

Hazardous Polymerization
Hazardous polymerization does not occur.

Conditions to avoid
Heat, flames and sparks.

Incompatible materials
Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products
Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.
.

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.

Eye Contact Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain.

Skin Contact Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. Repeated exposure may cause skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Harmful if swallowed. (based on components).

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz 14808-60-7	= 500 mg/kg (Rat)	-	-
Petroleum naphtha, light aromatic 64742-95-6	-	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h = 3400 ppm (Rat) 4 h

1,2,4 Trimethylbenzene 95-63-6	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m^3 (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
1,3,5-Trimethylbenzene 108-67-8	-	-	= 24 g/m^3 (Rat) 4 h
Xylene, mixed isomers 1330-20-7	= 4300 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	-

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects There is no data available for this product.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	X
Titanium dioxide 13463-67-7		Group 2B		X
Xylene, mixed isomers 1330-20-7		Group 3		
Cumene 98-82-8		Group 2B		

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP (National Toxicology Program)
Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. More detailed substance and/or ingredient information may be provided in the other sections of this SDS.

Chronic Toxicity	Possible risk of irreversible effects. Aspiration may cause pulmonary edema and pneumonitis. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected carcinogen. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Kidney. Lungs. Liver.

Aspiration Hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
867.00 mg/kg
ATEmix (inhalation-gas)
87,000.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
28.41 mg/l
ATEmix (inhalation-vapor)
213.00 ATEmix

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT

Ecotoxicity
Toxic to aquatic life with long lasting effects.

Persistence and Degradability
No information available.

Bioaccumulation

Chemical Name	Log Pow
1,2,4 Trimethylbenzene 95-63-6	3.63
Xylene, mixed isomers 1330-20-7	3.15
Cumene 98-82-8	3.55

Other adverse effects
No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of in accordance with local regulations.

US EPA Waste Number D001 U055 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene, mixed isomers 1330-20-7				U239
Cumene 98-82-8				U055

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
1,2,4 Trimethylbenzene 95-63-6	Toxic
Xylene, mixed isomers 1330-20-7	Toxic Ignitable
Cumene 98-82-8	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to DOT
Description CONSUMER COMMODITY, ORM-D, MARINE POLLUTANT
Emergency Response Guide Number 128

TDG

UN-No UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Description UN1263, PAINT, 3, III

MEX

UN-No UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Description UN1263 PAINT, 3, III

ICAO

UN-No UN1263

Proper Shipping Name	PAINT RELATED MATERIAL
Hazard Class	3
Packing Group	III
Description	UN1263, PAINT RELATED MATERIAL, 3, III

IATA

UN-No	UN1263
Proper Shipping Name	PAINT RELATED MATERIAL
Hazard Class	3
Packing Group	III
Description	UN1263, PAINT RELATED MATERIAL, 3, III

IMDG/IMO

UN-No	UN1263
Proper Shipping Name	PAINT
Hazard Class	3
Packing Group	III
EmS No.	F-E, S-E
Description	UN1263, PAINT, 3, III, FP 40C

RID

UN-No	UN1263
Proper Shipping Name	PAINT
Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1263 PAINT, 3, III

ADR

UN-No	UN1263
Proper Shipping Name	PAINT
Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1263 PAINT, 3, III

ADN

UN-No	UN1263
Proper Shipping Name	PAINT
Hazard Class	3
Packing Group	III
Classification Code	F1
Special Provisions	163, 640E, 650
Description	UN1263 PAINT, 3, III
Hazard Labels	3
Limited Quantity	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	95-63-6	1 - 5	1.0
Cumene - 98-82-8	98-82-8	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Cumene 98-82-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Quartz - 14808-60-7	Carcinogen
Titanium dioxide - 13463-67-7	Carcinogen
Cumene - 98-82-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Portland cement 65997-15-1	X	X	X		
Quartz 14808-60-7	X	X	X		
Stoddard solvent 8052-41-3	X	X	X		
Limestone 1317-65-3	X	X	X		
Mica 12001-26-2	X	X	X		
1,2,4 Trimethylbenzene 95-63-6	X	X	X	X	X
Titanium dioxide 13463-67-7	X	X	X		
Perlite 93763-70-3	X	X	X		
1,3,5-Trimethylbenzene 108-67-8	X	X	X		X

Xylene, mixed isomers 1330-20-7		X		X	
Cumene 98-82-8	X	X	X	X	X

International Regulations

Mexico
National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Portland cement 65997-15-1 (10 - 30)		Mexico: TWA 10 mg/m^3 Mexico: STEL 20 mg/m^3
Quartz 14808-60-7 (10 - 30)		Mexico: TWA= 0.1 mg/m^3
Stoddard solvent 8052-41-3 (10 - 30)		Mexico: TWA 100 ppm Mexico: TWA 523 mg/m^3 Mexico: STEL 200 ppm Mexico: STEL 1050 mg/m^3
Limestone 1317-65-3 (5 - 10)		Mexico: TWA= 10 mg/m^3 Mexico: STEL= 20 mg/m^3
Mica 12001-26-2 (1 - 5)		Mexico: TWA= 3 mg/m^3
1,2,4 Trimethylbenzene 95-63-6 (1 - 5)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m^3 Mexico: STEL 35 ppm Mexico: STEL 170 mg/m^3
Titanium dioxide 13463-67-7 (1 - 5)		Mexico: TWA= 10 mg/m^3 Mexico: STEL= 20 mg/m^3
Perlite 93763-70-3 (1 - 5)		Mexico: TWA 10 mg/m^3
1,3,5-Trimethylbenzene 108-67-8 (1 - 5)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m^3 Mexico: STEL 35 ppm Mexico: STEL 170 mg/m^3
Xylene, mixed isomers 1330-20-7 (0.1 - 1)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m^3 Mexico: STEL 150 ppm Mexico: STEL 655 mg/m^3
Cumene 98-82-8 (0.1 - 1)		Mexico: TWA 50 ppm Mexico: TWA 245 mg/m^3 Mexico: STEL 75 ppm Mexico: STEL 365 mg/m^3

Mexico - Occupational Exposure Limits - Carcinogens

Canada
WHMIS Hazard Class
B3 - Combustible liquid
D2A - Very toxic materials

16. OTHER INFORMATION

NFPA	**Health Hazard** 2	**Flammability** 2	**Instability** 0	**Physical and Chemical Hazards** -
HMIS	**Health Hazard** 2 *	**Flammability** 2	**Physical Hazard** 0	**Personal Protection** X

Chronic Hazard Star Legend ** = Chronic Health Hazard*

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Revision Date	14-Jan-2014
Revision Note	No information available.

General Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet